Digital Thermometer (TM6801B)

Features

Digital thermometer provide fast and accurate temperature measurement for a variety of applications. Many different styles of probes are available to suit almost any kind of job in which contact thermomenters are used. Air and gas temperatures, internal food temperatures, and surface temperatures in both industrial and commercial environments can be made using these instruments. Most units are provided with miniature plug connector, a single unit can be used with a variety of probes.



Specification

Model	TM6801B
Temperture Range	0℃~1300℃, 32°F~1999°F
Resolution	0.1℃ or 0.1°F
Accuracy	0℃~1300℃, ± 0.3%rdg +1℃ 32°F~1999°F, ± 0.3%rdg +1°F
Input Signal	K

Digital Thermometer (TM1310)



Specification

Model	TM1310
Temperture Range	0℃~1300℃, 32°F~1999°F
Resolution	0.1℃ or 0.1°F
Accuracy	0℃~1300℃, ± 0.3%rdg +1℃ 32°F~1999°F, ± 0.3%rdg +1°F
Input Signal	K

Digital Thermometer (TM1320)



Specification

Model	TM1320
Temperture Range	0℃~1300℃, 32°F~1999°F
Resolution	0.1℃ or 0.1°F
Accuracy	0℃~1300℃, ± 0.3%rdg +1℃ 32°F~1999°F, ± 0.3%rdg +1°F
Input Signal	K

ZONZEN

Precision Thermometer

Features

80 series hand held digital thermometer with micro PC & 60mm×50mm large LCD display and double 4 1/2-digit display, input signal choice of T1 & T2.

- Logging: Provided with time period programmable
- Input: Thermocouple (K, J, T, E, S, N) / RTD (PT100)
- Accuracy: ±0.3%+0.5℃
- Resolution: 0.1℃, 0.1℉ (< 2000) 1℃, 1℉ (≥ 2000)
- Communication interface: RS232



82 II

Infrared Thermometer

Features

Infrared thermometer is a type of non-contact temperature detector, which are widely used in temperature detection in areas including maintenance of electrical equipments, detection of auto maintenance, food safety inspection, examination of heating spot, heat supply, and communication, refrigeration and fire-prevention operation.



SM580

Specification

Model	SM380	SM580
Temperature Range	-32℃~380℃, -25℉~716℉	-32℃~580℃, -25℉~1076℉
Measurement Accuracy	±2℃ (±4℉)	±2℃ (±4℉)
Repeat Accuracy	±1℃ (±2℉)	±1℃ (±2℉)
Measuring Distance Ratio	12:1	12:1
Resolution	0.1℃ / 0.1℉	0.1℃ / 0.1℉
Emissivity	0.95	0.95